



序号	型号 (Type)	料号 (PART NO)	螺纹规格 Thread size
1	H16B-CCTH-2L-M25	19300160736	M25
2	H16B-CCTH-2L-M32	19300160737	M32
3	H16B-CCTH-2L-M40	19300160738	M40
4	H16B-CCTH-2L-PG21	09300160730	PG21
5	H16B-CCTH-2L-PG29	09300160731	PG29

技术参数:

- 材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: Grey (灰色)
- 温度范围: -40℃ - +125℃
- 防护等级: IP65 (联锁状态, IEC 60529)
- 联锁元件:
 - 锁扣方式: 金属双扣
 - 材料: 不锈钢
- 出线方向: 顶出线
- 出线孔数: 1
- 螺纹规格: M/PG
- 密封元件: NBR

Technical specification:

- Material: Aluminium die-cast
- Surface: powder-coated
- Colour: (grey)
- Temperature range:
 - 40℃ - +125℃
- Degree of Protection: IP65
(acc.to IEC 60529 for coupled connector)
- Locking element:
 - locking type: double locking latch
 - material: stainless steel
- Cable entry: top entry
- No. of cable entries: 1
- Thread size: M/PG
- Hoods/Housings sealing: NBR

ZJK 浙江昊科电气有限公司 ZHEJIANG HAOKO ELECTRICAL CO.,LTD		图号 Drawing No:	/
产品代号 Part Code:		产品料号 PART NO:	/
日期 Date:	2020.8.28	数量 Qty	绘图 Drawn
比例 Scale	1.5:1	重量 Weight	页 SHEET
版本 REV	HK-1	数量 Qty	1/1
All Dimensions in mm Original Size DIN A 4		数量 Qty	Tang