



序号	型号 (Type)	料号 (PART NO)	螺纹规格 Thread size
1	H32B-TE-2B-M32	19300320447	M32
2	H32B-TE-2B-M40	19300320448	M40
3	H32B-TE-2B-M50	19300320449	M50
4	H32B-TE-2B-PG29	09300320441	PG29
5	H32B-TE-2B-PG36	09300320442	PG36
6	H32B-TE-2B-PG42	09300320443	PG42

技术参数：
 - 材料：压铸铝
 - 表面处理：粉末喷涂
 - 颜色：Grey (灰色)
 - 温度范围：-40℃ - +125℃
 - 防护等级：IP65 (连锁状态, IEC 60529)
 - 出线方向：顶出线
 - 出线孔数：1
 - 螺纹规格：M/PG

Technical specification:
 - Material: Aluminium die-cast
 - Surface: powder-coated
 - Colour: (grey)
 - Temperature range:
 -40℃ - +125℃
 - Degree of Protection: IP65
 (acc.to IEC 60529 for coupled connector)
 - Cable entry: top entry
 - No. of cable entries: 1
 - Thread size: M/PG

浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO., LTD		图号 Drawing No:		/			
产品代号 Part Code:		H32B-TE-2B-M/PG		产品料号 PART NO:		/	
Date:	2019.02.10	Scale	REV	Weight	Qty	Drawn:	SHEET
	All Dimensions in mm Original Size DIN A 4	1:2	HK-1	/	/	Tang	1/1