



序号	型号 (Type)	料号 (PART NO)	螺纹规格 Thread size
1	H24B-TEH-2L-M32	19300240437	M32
2	H24B-TEH-2L-M40	19300240438	M40
3	H24B-TEH-2L-PG21	09300240430	PG21
4	H24B-TEH-2L-PG29	09300240431	PG29

- 技术参数:
- 材料: 压铸铝
  - 表面处理: 粉末喷涂
  - 颜色: Grey (灰色)
  - 温度范围: -40°C - +125°C
  - 防护等级: IP65 (联锁状态, IEC 60529)
  - 联锁元件:
    - 锁扣方式: 金属双扣
    - 材料: 不锈钢
  - 出线方向: 顶出线
  - 出线孔数: 1
  - 螺纹规格: M/PG

- Technical specification:
- Material: Aluminium die-cast
  - Surface: powder-coated
  - Colour: (grey)
  - Temperature range:
    - 40°C - +125°C
  - Degree of Protection: IP65  
(acc.to IEC 60529 for coupled connector)
  - Locking element:
    - locking type: double locking latch
    - material: stainless steel
  - Cable entry: top entry
  - No. of cable entries: 1
  - Thread size: M/PG

		浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO.,LTD		图号 Drawing No: /			
产品代号 Part Code:		H24B-TEH-2L-M/PG		产品料号 PART NO: /			
Date:	2018.09.26	Scale	REV	Weight	Qty	Drawn:	SHEET
	All Dimensions in mm Original Size DIN A 4	1:2	HK-1	/	/	Tang	1/1