



| 序号 | 型号 (Type) | 料号 (PART NO) | 螺纹规格 Thread size |
|----|------------------|--------------|---------------------|
| 1 | H24B-SF-2L-2M25 | 19300241271 | M25 |
| 2 | H24B-SF-2L-2PG21 | 09300241270 | PG21 |

技术参数:

- 材料: 压铸铝
- 表面处理: 粉末喷涂
- 颜色: Grey (灰色)
- 温度范围: -40°C - +125°C
- 防护等级: IP65 (联锁状态, IEC 60529)
- 联锁元件:
 - 锁扣方式: 金属双扣
 - 材料: 不锈钢
- 出线方向: 侧出线
- 出线孔数: 2
- 螺纹规格: M/PG
- 密封元件: NBR

Technical specification:

- Material: Aluminium die-cast
- Surface: powder-coated
- Colour: (grey)
- Temperature range:
 - 40°C - +125°C
- Degree of Protection: IP65
(acc.to IEC 60529 for coupled connector)
- Locking element:
 - locking type: double locking latch
 - material: stainless steel
- Cable entry: side entry
- No. of cable entries: 2
- Thread size: M/PG
- Hoods/Housings sealing: NBR

| | | | | | | | |
|---|---|-------------------|------|--------|-----|--------|-------|
| ZJKK 浙江昊科电气有限公司 ZHEJIANG HAOKE ELECTRICAL CO.,LTD | | 图号 Drawing No: | | / | | | |
| 产品代号 Part Code: H24B-SF-2L-2M/2PG | | 产品料号 PART NO: | | / | | | |
| Date: | 2018.08.10 | Scale | REV | Weight | Qty | Drawn: | SHEET |
| | All Dimensions in mm Original Size DIN A 4 | 1:1 | HK-1 | / | / | Tang | 1/1 |